

Specifications

(Ver. 1.00)

Product Name: WATCH BOOT

Model Number: RPC-M5C-EA

■ Network Specifications

Protocol: ARP、TCP、UDP、IP、ICMP、SMTP、POP3、APOP、IMAP、
BOOTP、DHCP、TELNET、HTTP、NTP、SNMP、WOL

Interface:

Ethernet: LAN×1 (RJ-45) : 10BASE-T/100BASE-TX

■ Power Control Interface Specifications

Ethernet: WEB、TELNET、E-mail、SNMP

Schedule: Weekly (up to 20 settings) *Must be connected to an NTP Server

■ Function Specifications

Display/indication Functions: 7 LEDs indicate status for main power, individual outlets, and LAN connection

Alive Monitoring Functions: Ping monitoring, Heartbeat monitoring, and linked outlet power control.

Power Control Functions: 4 outlets featuring individual power control

Status Notification Functions: SNMP、E-mail、MSRP (Developed by Meikyo Co. LTD)

WOL Functions: Magic Packet sent when outlet power is turned ON

*REBOOT (Turns the outlet ON after said outlet is turned OFF)

■ Hardware Specifications

Outlets: 4

Maximum Control Output: 12A

Maximum Power Consumption: 5.8W

Input Voltage: AC100-120V 50/60Hz

Operating Temperature: 0~40 degrees Celsius

Operating Humidity: 20~85% (without condensation)

Dimensions: 220 (W) x 45 (H) x 170 (D) millimeters

Weight: 3.5lbs (1.6kg)

Protection Circuit: Fused (15 Amp)

Surge Absorber (line-neutral, line-ground)

■ Accessories Specifications

Accessories: 1 User's Manual/Warranty, 1 Power Cord

■ Standards: FCC Part15 Subpart B, UL60950-1

RoHS Compliant