



# GEIST

## PDU 検索について

# GEISTホームページからPDU検索



ホームページ

www.geistglobal.com

## Geist Data Center Solutions

Geist is a leading data center provider for power strips, monitoring equipment, cabinet containment and in-rack cooling, and DCIM systems. Geist's power strips are tailored to meet each client's needs and provide unbeatable performance in the data center. Our industry leading monitoring and cooling solutions increase data center efficiencies and make going green easier than ever before.

With over 450 instances of our DCIM software installed on five continents monitoring over 500,000 equipment cabinets in 1,500 environments, Geist creates comprehensive data aggregation systems that automate data center reporting and provide critical infrastructure management tools. Our two data center monitoring and management systems, Environet and Racknet, fit all needs from power strip aggregation to enterprise level DCIM systems.

Our customer focus has motivated Geist to become a world leader in designing and manufacturing sophisticated data center management solutions for the four cornerstones of operations – power, cool, monitor and manage.

### LATEST GEIST NEWS:

More Value to Customers with Launch of ITWatchDogs by Geist - [Read More](#)

Geist DCIM Reveals Environet Asset to Expand Infrastructure Solutions - [Read More](#)

Geist unveils next generation technology platform for its Power Distribution Units to meet latest enterprise data center and cloud service provider demands - [Read More](#)

@geistglobal Twitter

Come hear our cool at Green Data Center Conference. We're talking on Day 2. Good info you won't want to miss. #DynamicContainment #GDCCON — 1 day 3 hours ago

Via: DATACENTRE.ME #blog: "The Internet of Things and the Loss of Privacy" <http://t.co/trhpNqdWf> #secureIT #DCME — 1 day 3 hours ago

2015 Data Center 100 features one of our own! check out who it is! #DCIM #datacenter <http://t.co/1V4HJYUG38P> — 1 day 3 hours ago

Green Data Center Conference Feb 23-25. Sunny and 75. Of course, we'll be there! #GDCCON #datacenter #cooling — 2 days 1 hour ago



PDU 検索サイト



# 使用国(Japan)を選択



Sign In | Contact Us

USA: 800.432.3219 USA: +1.402.474.3400 UK: +44.1823.275100 ASIA: +86.755.86639505

Home Products Solutions News Events Partners Support About Us Contact Us

Search...



Home >



## Select your country

All

Europe

Austria  
Belarus  
Belgium  
Bulgaria  
Cyprus  
Czech  
Denmark  
Estonia  
Finland  
France  
Germany  
Greece  
Hungary  
Iceland

Ireland

Italy  
Kazakhstan  
Latvia  
Liechtenstein  
Lithuania  
Luxembourg  
Malta  
Netherlands  
Norway  
Poland  
Portugal  
Romania  
Russia

Slovakia

Slovenia  
Spain  
Sweden  
Switzerland  
Turkey  
UK

Asia

China  
Hong Kong  
India  
Japan  
Malaysia  
Singapore

South America

Brazil

Paraguay

Peru  
Uruguay

North America

Canada  
Mexico  
US

Australia

Australia  
New Zealand  
New Zealand

Africa

U.A.E



# 現在の日本向け標準製品数



Sign In | Contact Us

USA: 800.432.3219 USA: +1.402.474.3400 UK: +44.1823.275100 ASIA: +86.755.86639505

Home Products Solutions News Events Partners Support About Us Contact Us

Search...

Home >

Advanced Search

PDU Type All Amps All Volts All kW Plug Type Configuration Length Search

NEW SEARCH

Plug Form ALL Receptacle Type ALL Total Receptacle Local Display Switch Breaker Environmental Monitoring Japan

Filters (Clear): Country: Japan x

Viewing products available in: Japan

最初にNew Serchをクリック

Products found: 32

Item #	Sub Category	Amps	Volts	Rackmount Length	Cord Length	Plug Type	Receptacle (Qty)	Local Meter	Enviro Monitor	Specs
P1000 -- PXPBM300-103IN6JL6	Unit Level	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1001 -- PVHBMN302-102IN6JS6	Unit Level	20A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1002 -- PJBMN302-102IN6JS5	Unit Level	20A	100V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1003 -- PXPBM300-103IN6JL5	Unit Level	30A	100V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1009 -- PVHBMN308-102IN6JL15	Unit Level	20A	200V DELTA	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	





# PDU 検索

<例>

縦型の30A, 200V

レセプタクルはC13

電力監視機能と各種センサー入力ポート付き

# PDU 検索

構成(Configuration)から  
縦型(Vertical)を選択

GEIST

USA: 800.432.3219 USA: +1.402.474.3400 UK: +44.1823.275100 ASIA: +86.755.86639505

Home Products Solutions News Events Partners Support About Us Contact Us Search...

Advanced Search

PDU Type All Amps All Volts All kW Plug Type Configuration Length Search

Configuration  
Horizontal  
Horizontal/Vertical  
Other  
Vertical

NEW SEARCH

Plug Form: ALL Receptacle Type: ALL Total Receptacle Local Display Horizontal Monitoring Japan

Filters (Clear): Country: Japan

Viewing products available in: Japan

Products found: 32

Item #	Sub-Category	Amps	Volts	Rackmount Length	Cord Length	Plug Type	Receptacle (Qty)	Local Meter	Enviro Monitor	Specs
P1000 -- PXPBM300-103IN6JL6	Unit Level	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1001 -- PPHVBMN300-102IN6J56	Unit Level	20A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1002 -- PJBMM300-102IN6J55	Unit Level	30A	100V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	



# PDU 検索

USA: 800.432.3219 USA: +1.402.474.3400 UK: +44.1823.275100 ASIA: +86.755.86639505

Home Products Solutions News Events Partners Support About Us Contact Us Search...

Advanced Search: PDU Type, All Amps, All Volts, All kW, Plug Type, Vertical, Length

Filters (Clear): Cou, Viewing products available

Item #	Amps	Volts	Rackmount Length	Cord Length	Plug Type	Receptacle (Qty)	Local Meter	Enviro Monitor	Specs
P1000 -- PXPBM300-103M	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1001 -- PVPVBM300-103M	20A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1002 -- PJBMM300-102M	20A	100V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1003 -- PXPBM300-103M	30A 120V	100V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1008 -- PVPVBM300-103M	20A	200V DELTA	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1010 -- PXPBM300-103M	30A	200V DELTA	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1011 -- PZPBM248-106H6PS15-	48A	200V	66 in / 1682 mm	3 m	IEC	IEC C13 (18)	Yes	No	

電流(All Amps)から30Aを選択

# PDU 検索



USA: 800.432.3219 USA: +1.402.474.3400 UK: +44.1823.275100 ASIA: +86.755.86639505

Home Products Solutions News Events Partners Support About Us Contact Us Search...

Home >

PDU Type 30A All Volts All kW Plug Type Vertical Length Search

Advanced Search

Plug Form ALL Receptacle Type ALL

Filters (Clear): Country: Japan x

Viewing products available in: Japan

NEW SEARCH

Display Switch Breaker Environmental Monitoring Japan

Products found: 19

Item #	Volts	Rackmount Length	Cord Length	Plug Type	Receptacle (Qty)	Local Meter	Enviro Monitor	Specs
P1000 -- PXPBM300-103IN6L6	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (8)	Yes	No	
P1005 -- PXPBM300-103IN6L5	100V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (8)	Yes	No	
P1010 -- PXPBM300-103IN6L15	200V DELTA	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (8)	Yes	No	
P1014 -- PRCKB300-103IN6L6-D	30A 200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (8)	Yes	Yes	

電圧(All Volts)から200Vを選択





# PDU 検索

GEIST USA: 800.432.3219 USA: +1.402.474.3400 UK: +44.1923.275100 ASIA: +86.755.86639501

Home Products Solutions News Events Partners Support About Us Contact Us Search...

PDU Type: 30A 200V All kW Plug Type: Vertical Length

Configuration: Vertical x Amps: 30A x Volts: 200V x

Item	Sub Category	Amps	Volts	Rackmount Length	Cord Length	Plug Type	Receptacle (Qty)	Local Meter	Enviro Monitor	Specs
P150	Transfer Switch	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P10	Power Monitoring	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	Yes	
P10	Outlet Level	30A	200V	70 in / 1778 mm	3 m	JIS	Locking IEC C13 (18) Locking IEC C19 (6)	Yes	Yes	
P10	Unit Level	30A	200V	70 in / 1778 mm	3 m	JIS	Locking IEC C13 (20) Locking IEC C19 (4)	Yes	Yes	
P150	Switched	30A	200V	70 in / 1778 mm	3 m	JIS	Locking IEC C13 (20) Locking IEC C19 (4)	Yes	Yes	
P10	Upgradeable	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P150	Basic	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	

電力監視は、一般的な電力監視とアップグレード可能なタイプの2種類あります。

PDU Typeから電力測定 (Power Monitoring)のユニットレベル(Unit Level)を選択

アップグレード可能なタイプは、まもなくセンサ入力ポート付きも発売されます。

# PDU 検索

センサー対応品(Enviromental Monitoring)からYesを選択

USA: 800.432.3219 USA: +1.402.474.3400 UK: +44.1823.275100 ASIA: +86.755.86639505

Home Products Solutions News Events Partners Support About Us Contact Us Search...

Home

- Unit Level 30A 200V All kW Plug Type Vertical Length Search

Advanced Search NEW SEARCH

Plug Form ALL Receptacle Type ALL Total Receptacle Local Display Switch Breaker Environmental Monitoring Japan

Filters (Clear): Country: Japan Configuration: Vertical Amps: 30A Volts: 200V PDU Type: Yes

Viewing products available in: Japan Products found: 3

Item #	Sub Category	Amps	Volts	Rackmount Length	Cord Length	Plug Type	Receptacle (Qty)	Local Meter	Enviro Monitor	Specs
P1014 -- PRC3B300-103IN6JL6-D	Unit Level	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	Yes	
P1036 -- PRC3W300-103PN6JL6-D-LP	Unit Level	30A	200V	72 in / 1829 mm	3 m	JIS	Locking IEC C13 (24) Locking IEC C19 (6)	Yes	Yes	
P1038 -- PRC3W420-103Z6JL6-D-LP	Unit Level	30A	200V	70 in / 1778 mm	3 m	JIS	IEC C13 (36) IEC C19 (6)	Yes	Yes	

# PDU 検索



Sign In | Contact Us

USA: 800.432.3219 USA: +1.402.474.3400 UK: +44.1823.275100 ASIA: +86.755.86639505

Home Products Solutions News Events Partners Support About Us Contact Us

Search...

Home >

Advanced Search

- Unit Level 30A 200V All kW Plug Type Vertical Length Search

NEW SEARCH

Plug Form ALL Receptacle Type ALL Total Receptacle Local Display Switch Breaker Yes

Filters (Clear): Country: Japan x Configuration: Vertical x Amps: 30A x Volts: 200V x PDU Type: - Unit Level x

Environmental Monitoring: Yes x

Viewing products available in: Japan

P1014, P1036, P10383の3種類が該当しました。ここでロックタイプの選択も可能なことがわかります。

Products found: 3

Item #	Sub Category	Amps	Volts	Rackmount Length	Cord Length	Plug Type	Receptacle Qty	Local Meter	Enviro Monitor	Specs
<a href="#">P1014 -- PRCXB300-103IN6JL6-D</a>	Unit Level	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	Yes	
<a href="#">P1036 -- PRCXW300-103PN6JL6-D-LP</a>	Unit Level	30A	200V	72 in / 1829 mm	3 m	JIS	Locking IEC C13 (24) Locking IEC C19 (6)	Yes	Yes	
<a href="#">P1038 -- PRCXW420-103IZ6JL6-D-LP</a>	Unit Level	30A	200V	70 in / 1778 mm	3 m	JIS	IEC C13 (36) IEC C19 (6)	Yes	Yes	

各品番をクリックすると、それぞれの仕様一覧表を見ることができます。



このサイトからマニュアルや外形図等をダウンロードできます。

# PDU 検索



- Download Specification Sheet as PDF
- Download Product Manual
- Download Product Line Drawing
- Download Product Firmware

**Part Number** P1014 -- PRCXB300-103IN6JL6-D  
**Power Configuration** Power Monitoring, Unit Level  
**Physical Configuration** 30A, 200V, 6.0kW  
 66 in / 1682 mm Vertical



**Description** P1014 -- PRCXB300-103IN6JL6-D provides site managers with a comprehensive view of power usage in a data center. On-board and web power monitoring display options offer quick access to the unit's current, volts, real power, apparent power, power factor and kilowatt hours. By monitoring these critical variables, data center managers can evaluate energy usage trends and ensure maximum uptime. The unit's two environmental sensor ports also give data center managers the ability to track critical climate variables like temperature, air flow, humidity and dew point.

**Racknet Enabled** - The P1014 -- PRCXB300-103IN6JL6-D easily integrates with Racknet - Geist's DCIM software. Racknet (purchased separately), collects and reports critical power and environmental data for multiple PDUs in one, user configurable interface. Users gain immediate remote access to trends, alarms and histories of devices in the data center through a standard Web browser. Racknet saves both time and cost associated with managing each device individually. Contact your Geist rep for more details.

**Product Summary** P1014 -- PRCXB300-103IN6JL6-D - Power Monitoring, Unit Level, + Environmental Monitoring -- 30A, 200V, Vertical, (24) IEC C13, (8) IEC C19, breakered, 3 m power cord with L6-30P, Power - Local/Remote + Environmental Ports, Aggregate - Total Unit Monitoring (A, V, VA, W, kWh, PF), Circuit / Breaker Monitoring (A, V, W, VA, kWh, PF)

<b>Monitoring</b>	Power - Local/Remote + Environmental Ports
<b>Plug Form</b>	L6-30P
<b>Receptacle</b>	IEC C13 (Quantity: 24)  IEC C19 (Quantity: 8)

## P1014 -- PRCXB300-103IN6JL6-D - Product Specification and Options

<b>Monitoring</b>	Power - Local/Remote + Environmental Ports
<b>Monitoring Level 1</b>	Aggregate - Total Unit Monitoring (A, V, VA, W, kWh, PF)
<b>Monitoring Level 2</b>	Circuit / Breaker Monitoring (A, V, W, VA, kWh, PF)
<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	200V
<b>Current</b>	30A
<b>VA per Input (Load Capacity)</b>	6.0kW
<b>Frequency</b>	50/60 Hz
<b>Over Current Protection</b>	(2) 25A Double Pole Magnetic Breakers
<b>Switch</b>	Breaker/Switch Combination
<b>Activity LED</b>	1
<b>Idle LED</b>	1
<b>Power LED</b>	1
<b>Scrolling Digital Display</b>	Yes
<b>Power Cable Wire Gauge</b>	5.5mm <sup>2</sup>
<b>Power Cable Length</b>	3m
<b>Plug Type</b>	JIS C8303, 2P/3W, 30A, 250V Locking, NEMA L6-30P
<b>Combined Total Receptacle/Socket Quantity</b>	30
<b>Receptacle/Socket Type #1</b>	IEC C13
<b>Quantity on Face #1</b>	24
<b>Quantity per Breaker #1</b>	12
<b>Style #1</b>	Banks of 4
<b>Maximum Output per Receptacle/Socket #1</b>	15A
<b>Voltage per Receptacle/Socket #1</b>	200V
<b>Receptacle/Socket Type #2</b>	IEC C19
<b>Quantity on Face #2</b>	6
<b>Quantity per Breaker #2</b>	3
<b>Style #2</b>	Individual
<b>Maximum Output per Receptacle/Socket #2</b>	20A
<b>Voltage per Receptacle/Socket #2</b>	200V
<b>Internal RMS Voltage Sensor</b>	Yes
<b>Internal RMS Current Sensor</b>	Yes
<b>Network Connection</b>	Ethernet via RJ45
<b>Network Protocols Supported and Data Access Formats</b>	ARP, IPv4, IPv6, ICMP, ICMPv6, NCP, TCP, UDP, DNS, HTTP, HTTPS, SMTP, SMTPS, DHCP, SNMP, (v1/v2c/v3), Syslog, SSH, Serial, LDAP, J50N API, Web GUI, CLI, JSON datalog, CSV datalog
<b>Reboot Button</b>	Yes
<b>Serial Connection</b>	RS232 via RJ45
<b>Remote Sensor RJ Connection Jacks</b>	2
<b>RSD - Optional Remote Display Jack</b>	Yes
<b>Heavy Steel -Black Powder Coat</b>	Yes
<b>Configuration</b>	66 in / 1682mm Vertical Rackmount
<b>7938 Vertical Mounting Bracket KR</b>	Yes
<b>Toolless Mounting Hardware - Center to Center Spacing</b>	1566 mm and 1645 mm
<b>Made in the USA</b>	Yes
<b>Product Warranty</b>	Three Year
<b>Certification/Agency Approvals</b>	METI DENAN
<b>Certification/Agency Approvals</b>	RoHS Compliant
<b>Chassis Dimensions (LxWxD)</b>	1683mm x 511mm x 58mm
<b>Doghouse (D)</b>	37mm
<b>Shipped Weight</b>	17lbs (7.71kg)



# PDU 検索



Sign In | Contact Us

USA: 800.432.3219 USA: +1.402.474.3400 UK: +44.1823.275100 ASIA: +86.755.86639505

Home Products Solutions News Events Partners Support About Us Contact Us Search...

Home >

Advanced Search

PDU Type All Amps All Volts All kW Plug Type Configuration Length Search

NEW SEARCH

Plug Form ALL Receptacle Type ALL Total Receptacle Local Display Switch Breaker Environmental Monitoring Japan

Filters (Clear): Country: Japan x

Viewing products available in: Japan Products found: 32

Item #	Sub Category	Amps	Volts	Rackmount Length	Cord Length	Plug Type	Receptacle (Qty)	Local Meter	Enviro Monitor	Specs
P1000 -- PXPBM300-103IN6JL6	Unit Level	30A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1001 -- PVHVBMN302-102IN6JS6	Unit Level	20A	200V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1002 -- PJBMN302-102IN6JS5	Unit Level	20A	100V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1003 -- PXPBM300-103IN6JL5	Unit Level	30A	100V	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	
P1009 -- PVHVBMN308-102IN6JL15	Unit Level	20A	200V DELTA	66 in / 1682 mm	3 m	JIS	IEC C13 (24) IEC C19 (6)	Yes	No	

このように標準となるPDUを検索し、これらをベースにカスタム対応も可能。

